

# \*\*HARDWARE LOCATED INSIDE ROLLED PART OF TOP\*\*

## ASSEMBLY INSTRUCTIONS

1. Remove your existing hardware: front fender bolt, rear bumper nuts and bolts, and back support nuts and bolts.
2. Install the new hardware (supplied in kit) front fender hooks.



3. Install frame (with cloth cover and straps pre-assembled) by holding frame upright and sliding hinge bolts into the seat back support holes as shown. Be sure to slide the basket (if applicable) onto the bolts before assembling the washer and locknut.

**Important: Tighten all new hardware securely**

4. Assemble rear straps to rear bumper "eye" bolts. Tilt the frame backwards and let the rear frame unfold, then slip the loop at the end of each strap into the opening in the corresponding "eye" bolt.
5. Help needed on this step. Unfold the front top and slip the locking sleeve over the articulating hinge on each side of the front frame.
6. Attach the front straps to the front fender "eye" bolt with the snap clips on the straps. Adjust the tension on each strap by sliding the "H" clip up or down as needed to level and support your new top.
7. When the cover is folded down we suggest the banana bag cover that is included.

## USAGE AND CARE TIPS

1. Do not hold or lean on tops while riding golf cart.
2. Top and support structure are unable to support weight
3. During transportation, use bungees to secure the folded top to the golf cart.
4. Fold top down when transporting or loading your golf cart in a trailer/vehicle.
5. Keep your top clean at pivot points to ensure longevity.
6. Hand wash with mild soap and water only.

